



ALGA Microwave Inc.

www.ALGA.CA

Outdoor Ku-Band Upconverter (BUC)

2109 St-Regis

Dollard des Ormeaux, Quebec

H9B 2M9 Canada

Telephone: 514-683-6113

Facsimile: 514-683-3312

FEATURES:	Weatherproof Pressure tested up to 10 psi	Redundancy option
	Light weight & Compact	Overtemperature Shutdown

MODEL	OUTPUT POWER at PSAT typ. [Watts]	OUTPUT POWER at P1dB min [Watts] / [dBm]	GAIN, dB Min	POWER CONSUMPTION [Watts]	Weight [lbs / kgs]	SIZE Length X Width X Height [Inches]
NJALKU-12	12	10 W / 40 dBm	60	150	15 / 7	10.9 X 9.7 X 5.3 (FANLESS)
NJALKU-16	16	12 W / 41 dBm	70	170	15 / 7	10.9 X 9.7 X 5.3 (FANLESS)
NJALKU-20	20	16 W / 42 dBm	70	250	22 / 10	10.9 X 9.7 X 8.7
NJALKU-25	25	20 W / 43 dBm	70	300	22 / 10	10.9 X 9.7 X 8.7
NJALKU-30	30	25 W / 44 dBm	70	350	22 / 10	10.9 X 9.7 X 8.7
NJALKU-50	50	40 W / 46 dBm	80	600	31 / 14	12.7 X 10.7 X 10.7
NJALKU-60	60	50 W / 47 dBm	80	650	31 / 14	12.7 X 10.7 X 10.7
NJALKU-100	100	80 W / 49 dBm	80	1200	74 / 34	16.5 X 15.4 X 9.2

ELECTRICAL CHARACTERISTICS		TECHNICAL SPECIFICATIONS	
Output Frequency Range,	see options	14.00 to 14.50 GHz,	options XXX
Input Frequency Range		950 to 1450 MHz,	
Gain flatness over any 40 MHz		+/-1.0 dB max at room temperature	
Gain flatness over full band		+/-2.5 dB max at room temperature	
Gain Variation		± 2.5 dB over operating temperature range	
Input VSWR (L-Band)		2.0 : 1, max	
Output Return Loss (Ku-Band)		-17dB, max	
Spurious at rated power		-50 dBc max.	
Third order IMD (two equal tones 5Mhz apart)		-33dBc max. @ 7dB back off from rated P1dB, -25dBc max. @ 3dB back off from rated P1dB	
Output Phase Noise		@ 1KHz	-70 dBc / Hz
		@ 10 KHz	-80 dBc / Hz
		@ 100 KHz	-90 dBc / Hz

POWER REQUIREMENTS	
Input supply voltage	see options
	110/220 VAC ±15% (47-63 HZ) Auto Ranging 48 VDC optional for certain models

MECHANICAL CHARACTERISTICS	
IF input (L-Band) Interface	Type N Connector (Type F Connector Optional)
RF output (Ku-Band) Interface	WR75 Grooved
Power Input	MS3102R16-10P
M&C Interface	MS3102R20-29S
Redundant Interface	MS3102R18-1S
Temperature Operating	-40° C to +55°C
Storage	-55°C to +85°C
Humidity	100%, considering, rain 2" per hour
Altitude	10000' AMSL

Options (XXX)	Output Frequency	(X) 13.75 - 14.5 GHz	(X) 13.75 - 14.25 GHz	(X) Other
	Power Supply	110 / 220 VAC	(X) 48 VDC	(X) Other
	Input Connector	N-Type	(X) F-Type	(X) Other
	Output Connector	WR-75 Grooved	(X) N-Type	(X) Other
	M & C Interface	Analog (TTL)	(X) Digital (RS 232 or 485)	(X) Other
M & C functions	Output Level control, RF Power detection, Temperature Monitor & Mute Control, etc...			

Note: The specifications are subject to change without notice.