

# UT-4579 X-Band Up Converter



## APPLICATION

The Comtech EF Data (CEFD) UT-4579 Up Converter is the ultimate in high performance and cost effective X-Band frequency conversion. The UT-4579 can be used for SCPC, DAMA, and TDMA, as well as full transponder HDTV and analog TV. Spectral purity, stability, and group delay characteristics fully meet or exceed the requirements of all domestic, international, and regional commercial satellite networks.

## HIGH GAIN

The UT-4579 has +13 dBm minimum output level at the 1 dB compression point and 35 dB of gain as a basic standard. These standard capabilities permit longer cable runs to the high power amplifier, or compensates for elaborate combining networks without adding expensive options such as external line amplifiers.

## LOW PHASE NOISE

The phase noise performance of the UT-4579 exceeds the Intelsat phase noise mask for IBS and IDR services by more than 9 dB. This allows phase high capacity earth stations to add more modulators and still meet transmission standards. The close-in phase noise is very low, making the converter ideal for low bit rate digital circuits such as those used in DAMA hub earth stations.

## REMOTE CONTROL

The remote control interface is selectable between EIA-232 and EIA-485. All configuration control, status retrieval, and adjustments are available as simple ASCII commands through the serial interface or through the front panel menu. As a cost option, the remote control command structure can be customized in order to accommodate existing network control software.

## DETACHABLE I/O MODULE

Each UT-4579 is equipped with a detachable I/O Module (IOM) that establishes input and output connections types. The module inserts into a rear compartment of the converter, and requires no additional outside space. The IOM includes a Type N connector for the RF path and a BNC connector at 50 or 75Ω for the IF path.

## DAISY CHAIN REDUNDANCY SWITCHING

The converter uses CEFD's proprietary "Daisy Chain" integrated switching technology. The Daisy Chain design removes the relays associated with a centralized protection switch tray and distributes them across the individual converters. CEFD was awarded patent 5,666,646 on this distributed protection switch topology.

Daisy Chain technology successfully eliminates a central switching chassis, two power supplies, a microprocessor, and several long, costly cables. Widely accepted in the industry, CEFD's Daisy Chain provides both pricing and marketing advantages.

## MINIMUM RACK SPACE

Due to its small rack height (1.75 inches) and the elimination of the space penalty paid for a separate 1+N switch chassis, the UT-4579 and the Daisy Chain switch architecture provide the most compact and cost effective converter subsystem available. The units are ideal for the construction of transportable systems such as "flyaways," and high capacity earth stations where space utilization and economy are prime considerations.

## UT-4579 X-Band Up Converter

### Specifications

Frequency Range	7900 to 8400 MHz
Conversion	Dual, No Inversion
Step Size	125 kHz standard, 1 kHz optional
Preset Channels	32 frequencies and gains
Stability Over Time	$\pm 1 \times 10^{-9}$ /Day
Stability Over Temp	$\pm 1 \times 10^{-8}$ 32 to 122°F (0 to 50°C)

### RF Input

Input Level	-45 dBm Typical
Return Loss	20 dB Minimum with I/O Module
Impedance	50Ω
Noise Figure	11 dB Maximum at 0 dB Attenuation

### IF Output

Level	+20 dBm at 1 dB Compression
Range	52 to 88 or 104 to 176 MHz Optional 50 to 90 MHz or 100 to 180 MHz (Contact factory with specific requirements)
Non-Carrier Spurious	-80 dBm
Carrier Spurious	-65 dBc at 0 dBm Output
Intermodulation	-60 dBc at 0 dBm Output SCL
Impedance	50 or 75Ω
Return Loss	23 dB Minimum with RF/IF Connector Module or SW Module

### Transfer

Gain	45 dB $\pm$ 2 dB
Attenuation Adjust	0 to 20 in 0.25 dB Steps 0.1 dB Steps Optional
Gain Stability	$\pm 0.25$ dB/Day
Ripple	$\pm 0.25$ dB ( $\pm 18$ MHz) Optional $\pm 20$ MHz 0.75 dB ( $\pm 36$ MHz) Optional $\pm 40$ MHz (Contact factory with specific requirements)
Slope	0.05 dB/MHz
Image Rejection	-80 dB In-Band
AM to PM	0.1°/dB for Output up to -5 dBm
IF Bandwidth	36 or 72 MHz, Optional 40 or 80 MHz (Contact factory with specific requirements)

### External Reference

	Input, either 5 or 10 MHz Option @ +3dBm Optional 10 MHz Rear Panel Reference Output
--	--

### Group Delay

Linear	0.03 ns/MHz
Parabolic	0.01 ns/MHz <sup>2</sup>
Ripple	1.0 ns Peak-to-Peak

Phase Noise	Limit (dBc/Hz)	Typical (dBc/Hz)
100 Hz	-69	-79
1 KHz	-79	-82
10 KHz	-89	-92
100 KHz	-100	-102
1 MHz	-110	-112

### Remote Control (Rear Panel)

	Comm Port RS-485 or RS-232C
--	-----------------------------

### Indicators (Front Panel)

Power On	Green LED
Mute	Yellow LED
Remote	Yellow LED
Reference	Yellow LED
Stored Fault	Red LED
Fault	Red LED

### Test Points (Front Panel)

RF Sample	SMA, -20 dBc Nominal
IF Sample	BNC, -20 dBc Nominal
Optional L.O. Sample	

### Power

Voltage	90 to 250 VAC Auto ranging, optional -48 VDC
Frequency	47 to 63 Hz
Dissipation	60 Watts

### Environmental

Temperature	32 to 122°F (0 to 50°C)
Altitude	10,000 Feet MSL
Humidity	0 to 95% Relative Humidity

### Physical

Dimensions (1RU)	19W x 1.75H x 22D Inches (48.30W x 4.45H x 55.90D cm)
Weight	15 Pounds (7.0 kg)

### MTBF

	49,740 hrs (calculated) > 100,000 hrs. (field experience)
--	--

### Summary Alarm

Relay Closure	Form C
---------------	--------

