

1.2M KU-BAND

RX/TX

SERIES

1134



Prodelin Corporation is the world's largest manufacturer of Rx/Tx VSAT antennas. We have the broadest product line in the industry including Receive Only, Rx/Tx and Rural Telephony antenna systems. Prodelin offers nineteen antenna sizes, 47cm to 4.5M. Prodelin is the leader in obtaining type certifications and approvals for Intelsat, AsiaSat and Eutelsat. Prodelin antennas provide the best quality in the market due to the sophisticated, precision SMC compression molding process technology. Prodelin provides the best value antenna solution to the market with competitive prices, the highest quality products and superb engineering support. Prodelin is ISO registered, KEMA # 70022.01. *Prodelin - The Market Leader in VSAT Antennas.*



Back View  
1.2M Rx/Tx



Option  
Feed Horn w/ OMT &  
Transmit Reject Filter

## Key Features

- IntelSat approval number IAO45A00
- AsiaSat approved
- EutelSat VSAT type approval
- ETSI Certification
- New optics for low cross-pol compliance
- Precision compression molded offset reflector
- Low cost shipping & easy local handling
- Simplified one-man installation - less than one hour assembly

Receive/Transmit

Series 1134

1.2M KU-BAND

RX/TX

SERIES

1134

## Electrical

Series 1134  
Ku-Band

Antenna Size		1.2 M (47 in.)
Operating Frequency (GHz)	Receive	10.95 - 12.75 GHz
	Transmit	13.75 - 14.5 GHz
Midband Gain ( $\pm$ .2dB)	Receive	41.5 dBi
	Transmit	43.0 dBi
Antenna Noise Temperature		
20° elevation		46 K
30° elevation		43 K
Sidelobe Envelope, Co-Pol (dBi)		
$1^\circ \leq \theta \leq 20^\circ$		29-25 Log $\theta$ dBi
$20^\circ < \theta < 26.3^\circ$		- 3.5 dBi
$26.3^\circ < \theta \leq 48^\circ$		32 -25 Log $\theta$ dBi
$48^\circ < \theta$		-10 dBi (averaged)
Cross-Polarization	Within 1 dB contour	-30 dB Max.
	Any Angle off Axis	-25 dB Max.
VSWR		1.3:1 Max.

## Mechanical

Reflector Material		Glass Fiber Reinforced Polyester SMC
Antenna Optics		Prime Focus, Offset Feed
Mast Pipe Size		2 1/2" SCH 40 Pipe (2.88" OD) 73.2 mm.
Elevation Adjustment Range		5° to 90° Continuous Fine Adjustment
Azimuth Adjustment Range		$\pm$ 20° Fine, 360° Continuous
Mount Type		Elevation over Azimuth
Shipping Specifications		90 lbs. (41 kg.)

## Environmental Performance

Wind Loading	Operational	50 mph (80 km/h)
	Survival	125 mph (201 km/h)
Temperature	Operational	-40° to 140° F (-40° to 60° C)
	Survival	-50° to 160° F (-46° to 71° C)
Rain	Operational	1/2" /hr
	Survival	2" /hr
Ice	Operational	-----
	Survival	1/2" radial
Atmospheric Conditions		Salt, Pollutants and Contaminants as Encountered in Coastal and Industrial Areas
Solar Radiation		360 BTU/h/ft <sup>2</sup>



1700 NE Cable Drive • Conover, NC 28613 USA  
 Tel: (828) 464-4141 • Fax: (828) 466-0860  
[www.prodelin.com](http://www.prodelin.com)

© Copyright 2000 Prodelin, a TriPoint Global Company.  
 All product specifications subject to change without notice.  
 The Prodelin logo is a trademark of TriPoint Global.