

IBUC Advantages

Integrated BUC/SSPA packaging for higher performance and reliability.

Guaranteed rated output power across the entire operating temperature range and frequency band.

Low phase noise exceeds IESS308/309 requirements by a minimum of 10dB.

NMS-friendly interfaces enable remote management of your earth station RF.

Embedded web pages provide management for small networks using any web browser.

AGC or ALC circuits hold gain or output level constant.

16dB User-adjustable gain in 0.1 dB steps preserves modem dynamic range.

Advanced customer interfaces:

- TCP/IP HTTP with embedded web pages.
- TELNET through TCP/IP
- FSK through TX IFL cable.
- RS232/485 serial port.
- Handheld terminal

1+1 switching logic and drivers built into the IBUC eliminate expensive external switching controller.

Extensive diagnostics displayed as web pages for faster setup and troubleshooting.



The revolutionary **IBUC** has advanced features to take your network to new heights.

Compared to traditional 70 MHz solutions, the **IBUC** offers significant benefits:

- Lower terminal cost
- Simpler design and installation
- Superior RF performance
- Simplified 1+1 configuration

New interfaces connect you to the **IBUC**'s extensive M&C facilities for network management or local access. This powerful new M&C enables:

- **Trouble free commissioning** with easy, point-and-click installation/configuration
- Continuous **verification** of performance with alarm history.
- Simplified **troubleshooting** of terminal faults.

IBUC comes with a complete set of diagnostic tools including:

- 10 MHz input detector
- Input voltage and current monitoring
- Transmit L-band input level detector
- Transmit RF output level detector
- Alarm history

As always, the **IBUC** carries Terrasat's guarantee of rated output power across the operating band and specified temperature range. Unique in the **IBUC** are internal AGC and ALC functions to satisfy demanding applications with stringent specifications.

The **IBUC** is manufactured in our modern Morgan Hill, CA facility to the same exacting quality processes as our PowerPlus series and OEM microwave products. Each unit undergoes rigorous testing, burn-in at elevated temperature, BER, and final testing over temperature so that you are assured of a high quality, reliable product.

For additional information contact Terrasat Sales at +1 408-782-5911 or by Email: Sales@Terrasatinc.com.

C-Band IBUC Block Upconverter Specifications

L-Band Input			External Reference (multiplexed on TX IFL)		
Frequency range			Frequency	10 MHz	
Band 1	950 to 1525 MHz		Level	-8 to +3 dBm	
Bands 2 & 3	1150 to 1450 MHz		Local Oscillator		
Band 4	950 to 1750 MHz		LO Frequency		
VSWR / Impedance	1.5:1 max / 50 ohms		Band 1	7375 MHz	
Connector	Type N female		Band 2	7875 MHz	
Input power detector range	-55 to -20 dBm		Band 3	8175 MHz	
Gain			Band 4	7600 MHz	
Small Signal Gain (L-band to RF) with attenuator set to 0 dB			Sense	Inverting	
5W	68 dB min		IBUC DC Supply		
10W	71 dB min		Multiplexed on TX IFL	5W, 10W	
20W	74 dB min		Connector	MS3102R14S-6P	
25W	75 dB min		Voltage / Current		
40W	77 dB min			+24 ± 4 VDC	+48 ± 11 VDC
60W	79 dB min		5W	3.0A @ 24VDC	1.5A @ 48VDC
80W	80 dB min		10W	4.5A @ 24VDC	2.0A @ 48VDC
Attenuator range	16 dB variable in 0.1dB steps		20W	na	4.0A @ 48VDC
Gain flatness	5 W to 40 W	60W to 80W & Band 4	25W	na	4.5A @ 48VDC
Full band	3 dB p-p max	4dB p-p max	40W	na	8.0A @ 48VDC
36 MHz	1dB p-p max	1.5 dB p-p max	60W	na	9.5A @ 48VDC
1 MHz	0.25 dB p-p	0.25 dB p-p	80W	na	11.5A @ 48VDC
Gain variation over temperature			Monitor and Control		
Open loop	3 dB p-p max	4 dB p-p max	FSK (multiplexed on TX IFL)		
With AGC	1 dB p-p max	1 dB p-p max	Transmitter		
RF Output			Frequency	650 kHz ± 5%	
Frequency range			Deviation	± 60 kHz	
Band 1 Standard C-Band	5850 to 6425 MHz		Output Level	-5 to -15 dBm (50 ohms)	
Band 2 Palapa/ST-1	6425 to 6725 MHz		Receiver		
Band 3 Insat	6725 to 7025 MHz		Nominal frequency	650 kHz	
Band 4 Extended C- Band	5850 to 6650 MHz		Locking range	± 32.5 kHz	
Interface	CPR-137G or N female, 50 ohm		Input sensitivity	-15 dBm	
VSWR	1.5:1 max		Interfaces (RS232, RS485, TCP/IP and Handheld Terminal)		
Rated output power (P1dB across temperature range and freq. band)			Connector	MS3112E-14-19S	
5W	+37 dBm min		RS232/485		
10W	+40 dBm min		Data Rate	Selectable 1.2 to 115.2 kbps	
20W	+43 dBm min		Data Format	8 bits, no parity, 1 stop bit, ASCII	
25W	+44 dBm min		Handheld Terminal data rate	9600 bps	
40W	+46 dBm min		TCP / IP	Telnet, HTTP	
60W	+47.8 dBm min		Environmental	<u>5 W to 40 W</u> <u>60W to 80W</u>	
80W	+49 dBm min		Operating temperature	-40°C to +60°C -40°C to +55°C	
IMD3 (2 carriers, 30 kHz apart, 9dB BO/carrier)	-32 dBc max		Relative humidity	100% condensing	
Level stability with ALC	± 0.5 dB		Altitude	15,000 ft., (5,000m) ASL	
Output power detector range	Rated power to -20 dB		Mechanical		
Power reading accuracy	+/- 1.0 dB max.			Size	Weight
Spurious	Complies with EN 301 443		5W, 10W	12.2"(L)x7.2"(W)x4.2"(H)	12 lbs
SSB Phase Noise				310mm x 183mm x 107mm	5.5 kg
Offset	External reference	IBUC	20-80W	12.2"(L)x7.2"(W)x8.4"(H)	17 lbs
10Hz	-120 dBc/Hz	-35 dBc/Hz		310mm x 183mm x 214mm	7.7 kg
100Hz	-130 dBc/Hz	-70 dBc/Hz			
1 kHz	-143 dBc/Hz	-80 dBc/Hz			
10 kHz	-152 dBc/Hz	-90 dBc/Hz			
100kHz	-155 dBc/Hz	-100 dBc/Hz			
1MHz	-155 dBc/Hz	-110 dBc/Hz			

Specifications are subject to change without notice



235 Vineyard Court
Morgan Hill, CA 95037
Tel. +1 408.782.5911
Fax: +1 408.782.5912
www.terrasatinc.com

C-Band IBUC Data Sheet 3/29/06